



**SFL**



2797 CPR 559419

**Declaration of Performance  
SIGMA 1mm & 0.6mm  
Connecting Flue Pipe**

**SIGMA DOP Issue 4  
BS EN 1856-2**

1. Unique identification code of the product-type:

**Single Wall Metal Connecting Flue Pipe  
EN 1856-2**

2. Type, batch or serial number or any other element allowing identification of the construction product as required under article 11(4):

Manufacturers Identification(s):

**SIGMA 0.6mm / 1.0mm**

Model 1 DN (127-203) T600 NI D V3 L50060 GXX NM

Model 2 DN (127-203) T600 NI D V3 L50100 GXX NM

XX relates to a distance of 3 x Pipe Diameter or minimum of 375mm at Ø125 and below.

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

**To convey the products of combustion from the heating appliance to the chimney**

4. Name, registered trade name or registered trade mark and contact address of the manufacture as required under article 11(5):

**SFL  
Pottington Business Park  
Barnstaple  
Devon  
United Kingdom  
EX31 1LZ  
Tel: 01271 326633 Fax: 01271 334303  
Email: [info@sflchimneys.com](mailto:info@sflchimneys.com) Web: [www.sflchimneys.com](http://www.sflchimneys.com)**

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks in article 12(2):

**N/A**

6. System of assessment and verification of consistency of performance as set out in CPR, Annex V:

**System 2+ and System 4 (Terminals)**

7. Notified factory production control certification body 2797 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity 2797 CPR 559419 of the factory production control.

**BSI Group The Netherlands B.V.**  
**John M. Keynesplein 9,**  
**1066 EP Amsterdam,**  
**The Netherlands.**

**Declared Performance to Annex ZA EN 1856-2**

	Essential Characteristics	Performance	Harmonised Technical Specifications
8.1	Compressive strength  Chimney sections, fittings and supports	Lengths Model 1,2 DN (127-203): 14m Tees Model 1,2 DN (127-203): 14m Supports NPD	EN 1856-2: 2009
8.2	Resistance to fire	Model 1 DN (127-203): T600 GXX NM Model 2 DN (127-203): T600 GXX NM XX = 3 x Pipe Diameter	
8.3	Gas tightness / leakage	Model 1,2 DN (127-203): N1	
8.4	Flow resistance of chimney sections  Flow resistance of chimney fittings	Mean Value of Roughness: 1mm  According to EN 13384-1	
8.5	Thermal resistance	0 m <sup>2</sup> K/W	
8.6	Thermal shock resistance  Sootfire resistance	Model 1,2 DN (127-203): Yes	
8.7	Thermal performance under normal operating conditions	Model 1,2 DN (127-203): T600	
8.8	Flexural tensile Strength  (only for means of connection for a chimney and fittings)	NPD	
8.9	Non vertical installations	Model 1,2 DN (127-203) 2m between lateral supports at 45°	
9.10	Components subject to wind load	NPD  Internal Connecting Flue Pipe	

8.11	Water and vapour diffusion resistance	Model 1,2 DN (127-203): No	EN 1856-2: 2009
8.12	Condensate penetration resistance.	Model 1,2 DN (127-203): No	
8.13	Durability against corrosion	Model 1,2 DN (127-203): V3 DRY	
8.14	Freeze thaw	Model 1,2 DN (127-203): Yes	

For further technical information, please refer to the product sales literature.

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Barnstaple, Devon 11/11/2024



.....  
**Flavio Buccianti - Managing Director**