



SFL

**UK
CA**
0168 CPR 91455

Declaration of Performance

Construction Products Regulation 2011 (retained EU law EUR 305/2011) as amended by the Construction Products (Amendment etc.) (EU Exit) Regulation 2019 and the Construction Products (Amendment etc.) (EU Exit) Regulation 2020

SIGMA 1mm & 0.6mm Connecting Flue Pipe

**SIGMA DOP Issue 5
BS EN 1856-2**



1. Unique identification code of the product-type:

**Single Wall Metal Connecting Flue Pipe
EN 1856-2**

2. Type, batch or serial number or any other element allowing identification of the construction product as required under article 11(4):

Manufacturers Identification(s):

SIGMA 0.6mm / 1.0mm

Model 1 DN (127-203) T600 NI D V3 L50060 GXX NM

Model 2 DN (127-203) T600 NI D V3 L50100 GXX NM

XX relates to a distance of 3 x Pipe Diameter or minimum of 375mm at Ø125 and below.

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

To convey the products of combustion from the heating appliance to the chimney

4. Name, registered trade name or registered trade mark and contact address of the manufacture as required under article 11(5):

**SFL
Pottington Business Park
Barnstaple
Devon
United Kingdom
EX31 1LZ
Tel: 01271 326633 Fax: 01271 334303
Email: info@sflchimneys.com Web: www.sflchimneys.com**

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks in article 12(2):

N/A

6. System of assessment and verification of consistency of performance as set out in CPR, Annex V:

System 2+ and System 4 (Terminals)

7. Notified factory production control certification body 0168 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity 0168 CPR 91455 of the factory production control.

TÜV Industrie Service GmbH TÜV Süd Gruppe
Ridlerstraße 65
D-80339 München

Declared Performance to Annex ZA EN 1856-2

	Essential Characteristics	Performance	Harmonised Technical Specifications
8.1	Compressive strength Chimney sections, fittings and supports	Lengths Model 1,2 DN (127-203): 14m Tees Model 1,2 DN (127-203): 14m Supports NPD	EN 1856-2: 2009
8.2	Resistance to fire	Model 1 DN (127-203): T600 GXX NM Model 2 DN (127-203): T600 GXX NM XX = 3 x Pipe Diameter	
8.3	Gas tightness / leakage	Model 1,2 DN (127-203): N1	
8.4	Flow resistance of chimney sections Flow resistance of chimney fittings	Mean Value of Roughness: 1mm According to EN 13384-1	
8.5	Thermal resistance	0 m ² K/W	
8.6	Thermal shock resistance Sootfire resistance	Model 1,2 DN (127-203): Yes	
8.7	Thermal performance under normal operating conditions	Model 1,2 DN (127-203): T600	
8.8	Flexural tensile Strength (only for means of connection for a chimney and fittings)	NPD	
8.9	Non vertical installations	Model 1,2 DN (127-203) 2m between lateral supports at 45°	
9.10	Components subject to wind load	NPD Internal Connecting Flue Pipe	

8.11	Water and vapour diffusion resistance	Model 1,2 DN (127-203): No	EN 1856-2: 2009
8.12	Condensate penetration resistance.	Model 1,2 DN (127-203): No	
8.13	Durability against corrosion	Model 1,2 DN (127-203): V3 DRY	
8.14	Freeze thaw	Model 1,2 DN (127-203): Yes	

For further technical information, please refer to the product sales literature.

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Barnstaple, Devon 03/03/2025



.....
Sami Caglar - Managing Director