Sflue

NEW Adjustable Slip Section

NOW AVAILABLE TO ORDER!

Introducing the **Adjustable Slip Section** for the SFlue brand; designed for use with a standard length to allow greater flexibility on site, where standard length configurations are not suitable for the required distance.

- **✓** Easy to install
- Aesthetical pleasing joint without the need for additional fixing such as screws or rivets
- ✓ Can be added to any preceading length
- **☑** Blanket insulation supplied
- ✓ Includes a Retention Band with adjustable lever toggle and bolt offering a secure structural clamp between the slip section and standard length.
- **✓** Also available in Satin Black finish









Call Customer Services on **01271 326633** or visit **www.sflchimneys.com** for more information.





Adjustable Slip Section

SPECIFICATIONS & PRICING

Adjustable limits of Slip Section when used with Standard Lengths

Dia Ø	Standard Sflue Lengths						
	300mm		500mm		1000mm		
	Minimum & Maximum Extension (mm)						
	MIN	MAX	MIN	MAX	MIN	MAX	
127	330	556	530	756	1030	1256	
152	330	544	530	744	1030	1244	

List Prices

Standard Finish

Part No.	Description	List Price £
2143005	Ø127MM SLIP SECTION ADJ LENGTH	102.01
2143006	Ø152MM SLIP SECTION ADJ LENGTH	110.34

Black Coated Finish

Part No.	Description	List Price £
2143005B	Ø127MM SLIP SECTION ADJ LENGTH (BLACK)	114.42
2143006B	Ø152MM SLIP SECTION ADJ LENGTH (BLACK)	123.91

IMPORTANT NOTE:

Adjustable Lengths and Slip Sections do not bear load. Always use a Wall Support Bracket or Support Plate immediately above the component when vertically applied.







