

FAQ



Is SFlue compatible with Nova?

SFL offer a Nova to SFlue adaptor as they have different couplers. Nova has a 16-barb coupler whereas SFlue only has 8. At 12 and 14 inches Sflue and Nova become compatible together as we use the same couplers for that diameter.

Which fuels can I use with SFlue?

SFlue is compatible with multi fuel systems including: wood burners, coal appliances, oil appliances and pellet stoves. We do not recommend you use petroleum coke or any smokeless fumes as they may contain halogens that can prematurely corrode the system.

Can I buy 7" & 8" SFlue?

SFL made the decision to stop stocking the 7" & 8" as standard due to the primary uses of SFlue not requiring such large diameters. We can however supply minimum order quantities if requested from customers services.

Can I use SFlue for a condensing appliance?

No SFlue is only to be used for negative pressure (dry) systems, there are no seals to protect from condensation and will be liable to corrosion damage. If you require a condensing flue system we offer Nova for twin wall and Supra+ for single wall.

FAQ

The logo for STOVE Sflue is located in the top right corner. It features the word "STOVE" in a small, white, sans-serif font above the word "Sflue" in a larger, white, sans-serif font. The text is set against a solid green rectangular background.

Can SFlue be used externally?

Yes SFlue can be used externally with lateral supports every 3 metres, we are confident in the insulation properties of SFlue and our brackets can hold over 100mph wind speeds comfortably.

Why can't I use the D5 firestop with SFlue?

The D5 firestop was designed for Nova, which uses metric dimensions whereas SFlue uses imperial dimension. The D5 is not applicable to the SFlue range due to the 2mm difference in dimension, technically it could be used but it would not be a clean fit.

The D5 however is being re-designed to be used in the SFlue range, along with:

- 500-850 adjustable length
- Short tapered adaptor
- Adjustable slip section
- Round top
- Storm cowl
- Galvanised wall support bracket
- Flex adaptors
- Galvanised wall sleeve
- Roof/rafter support

How do I fit Sflue?

SFlue is an 8 barb twist lock system that needs to be secured by locking bands, it has been designed specifically for ease of installation where no special tools are required.

How do I remove the appliance later?

The SFlue range has a number of adjustable components which are ideal for disconnecting the appliance whilst leaving the proceeding flue system unaffected.